



Model #: HV6002

Inlet/Outlet Connections:	¾" NPT (Inlet & Outlet)
Weight:	22lbs / 10kg
Pump Dimensions:	23" x 10" x 11" / 58cm x 25cm x 28cm
Shipping Box Dimensions:	25" x 25" x 20" / 63cm x 63cm x 50cm
Max Output:	25 GPM / 94 LPM
Pressure Range:	10-75 psi / 0.6-5 bar
Max Dilution:	(0.22oz/gallon) 1:580 / 0.15%
Min Dilution:	1:5,800 / 0.02%
Alternative Pump Head Materials:	Acrylic, PVC, HDPE, Kynar/PVDF
Alternative Seal Combinations:	Viton, EPDM, PAA
Alternative Chemical Cylinders:	SST, Hastelloy
Mounting Options:	Vertical or Horizontal Mount
Included Accessories:	Mounting Feet, Suction Hose, PVC Foot Valve, Operating Manual

Additional Options:

Hot Water Specific Machined Endplates (DMAC)

Support Documents:

- Schematic Print
- Operating Manual
- Installation Instructions (VM or HM)
- Dimensional Print

Recommended Accessories:

- Water Pressure Regulator
- Water Filter
- Mixing Chamber
- Backflow Preventer
- Rebuild Kit
- Anti-Siphon Kit

HYDROBLEND INTERNATIONAL CORPORATION

5301 Sawyer Ave * Boise, Idaho 83714 * USA * Ph (208) 375-5000, Fax (208) 378-9963 * Email sales@hydroblend.com
www.hydroblend.com US Pat. # 4,279,229 * US Pat. # 5,433,240 * US Pat. # 6,485,272 B2